



**ILLINOIS  
ENGINEERED  
PRODUCTS**

# Storefront Security Gates



- *Protect property and merchandise*
- *Custom built for an exact fit within 7-14 days*
- *Maintenance-free galvanized steel construction*
- *Powder coated colors available to coordinate with storefront's aesthetic*

**100% MADE IN  
AMERICA**


THE ONLY FOLDING GATES MADE WITH GALVANIZED STEEL

**54 YEARS**  
OF INNOVATION,  
QUALITY & SERVICE


# Storefront Folding Gates

## Hybrid Storefront Gate


Designed with a continuous frame on all sides with vertical bars and scissor style webbing for superior support and a high level of protection.




Single Gate: Fixed top track and fold away bottom track.  
Max Width: 16' | Max. Height: 12'




Single Gate: Fold away top track and fold away bottom track.  
Max Width: 16' | Max. Height: 7'6"




Pair Gate: Fixed top track and fold away bottom track.  
Max Width: 32' | Max. Height: 12'



Pair Gate: Fold away top track and fold away bottom track.  
Max Width: 32' | Max. Height: 7'6"




Fixed top track and fold away bottom track.




Fold away top track and fold away bottom track.

## LazyTong Storefront Top Track Gate

Gate hangs like a curtain across storefront and remains within top track for ease of use. Does not pivot out of opening.




Single Gate: Fixed top track.  
Max. Width: Unlimited  
Max. Height: 12'




Pair Gate: Fixed top track.  
Max. Width: Unlimited  
Max. Height: 12'

## LazyTong Storefront Bottom Track/Window Gate

When retracted, gate pivots 180 Degrees out of the opening and swings flat remaining virtually invisible while not in use.



Single Gate: Fixed bottom track.  
Max. Width: 8'  
Max. Height: 12' | Min. height: 31"



Pair Gate: Fixed bottom track.  
Max. Width: 16'  
Max. Height: 12' | Min. height: 31"

## Hybrid Specifications

**EXTRA HEAVY-DUTY**

Finish: Galvanized steel, unless otherwise noted.

Webbing: 3/8" x 3/4" 12 gauge u-channel riveted back to back with zinc plated rivets.

Vertical Channels: 1-1/4" x 5/8" 14 gauge c-channel.

Trolley: 1" diameter zinc plated steel wheels.

Top and Bottom Track: 1-7/8" x 1-5/16" 11 gauge box channel

Hinge Bar: 1-1/2" x 1-1/2" 12 gauge angle

Hinge: 4-1/2" x 4-1/2" x 3/16" thick, 3/8" pin.

Strap: 3/16" thick x 1-1/2" wide.

Locking: 1-7/8" x 1-5/16" 11 gauge box channel

Locking bar with padlock hasp.

Mounting: Jam mount or face mount.

Options: Galvanized steel with powder coating finish; Extra heavy-duty gate built with heavier gauge steel.

## LazyTong Specifications

**HEAVY-DUTY**

Finish: Galvanized steel, unless otherwise noted.

Webbing: 3/8" x 3/4" 14 gauge u-channel riveted back to back with zinc plated rivets.

Frame: 1-1/2" x 1-1/2" 12 gauge angle, zinc plated.

Trolley: 2" diameter zinc plated steel wheels.

Locking: 3/16" padlock hasp.

Standard Mounting Bracket: 2-1/2" x 7" "L" bracket, zinc plated.

Top Track Gate Mounting: Can be mounted higher than folding gate height. Can be face mounted to wall, mounted directly to ceiling or attached to free standing posts.

Bottom Track/Window Gate Mounting: Can be face mounted to wall.

Options: Galvanized steel with powder coating finish; Extra Heavy-duty gate built with heavier gauge steel.

## Accessories

Cylinder Lock: Pre-installed at the factory.

Padlock: 2" hardened steel with plated shackle.

8' Post: Mount gate to posts instead of wall or casing.

Illinois Engineered Products are only sold by Authorized Dealers



Tel. (55) 44 40 35 08  
E-mail. [servicio@dock-depot.com.mx](mailto:servicio@dock-depot.com.mx)  
Portal. [www.dock-depot.com.mx](http://www.dock-depot.com.mx)

EQUIPO DE ANDÉN Y PUERTAS INDUSTRIALES

