



**ILLINOIS
ENGINEERED
PRODUCTS**

Portable Gate Barrier Gate | Aisle Gate



- *Moveable access control and security*
- *High visibility*
- *Reduce liability occurrences*
- *Use one gate in multiple locations*

**100% MADE IN
AMERICA**

THE ONLY FOLDING GATES MADE WITH GALVANIZED STEEL

54 YEARS
OF INNOVATION,
QUALITY & SERVICE

Portable Gate

Galvanized Steel

Stock No.	Maximum Width	Collapsed Height	In-Use Height	Weight (lbs.)
Starter XL1265	up to 12'	6'6"	6'	135
Add-on XL665	adds 6'	6'6"	6'	64

Specifications

Finish: Galvanized steel.

Webbing: 14 gauge 3/8" x 3/4" u-channel riveted back to back with zinc plated rivets.

Vertical Frame: 12 gauge 1-1/2" x 1-1/2" angle.

Axles: 28" wide with 3" locking rubber casters.

Locking: Padlock hasp. Can be locked in place with wallmounted locking bars.

Starter: May be used alone, or to start a run of gates.

Add-on: Attaches to Starter Gate providing an additional 6' in width. Unlimited Add-on gates can be connected to a Starter Gate.

Options: Powder coating color; 7' in-use height gate and 8' in-use height gate, special order.

Aluminum

Call factory for specifications.

Stock No.	Maximum Width	Collapsed Height	In-Use Height	Weight (lbs.)
Starter XL1265AL	up to 12'	6'6"	6'	75
Add-on XL665AL	adds 6'	6'6"	6'	32

Portable and Barrier Gate Accessories

Padlock: 2" hardened steel with plated shackle.

8' Post: Lock gate to posts instead of wall or casing.



Starter Portable Gate



Starter Barrier Gate



Aisle Gate

Illinois Engineered Products are only sold by Authorized Dealers



DOCK-DEPOT
EQUIPO DE ANDÉN Y PUERTAS INDUSTRIALES

Tel. (55) 44 40 35 08
 E-mail. servicio@dock-depot.com.mx
 Portal. www.dock-depot.com.mx

Barrier Gate

Galvanized Steel

Stock No.	Maximum Width	Collapsed Height	In-Use Height	Weight (lbs.)
Starter XL1240	up to 12'	47"	41"	90
Add-on XL640	adds 6'	47"	41"	40

Specifications

Finish: Galvanized steel. Powder coated yellow & black.

Webbing: 14 gauge 3/8" x 3/4" u-channel riveted back to back with zinc plated rivets.

Vertical Frame: 12 gauge 1-1/2" x 1-1/2" angle.

Axles: 14" wide with 3" locking rubber casters.

Locking: Padlock hasp. Can be locked in place with wallmounted locking bars.

Starter: May be used alone, or to start a run of gates.

Add-on: Attaches to Starter Gate providing an additional 6' in width. Unlimited Add-on gates can be connected to a Starter Gate.

Option: Other powder coating colors.

Aluminum

Call factory for specifications.

Stock No.	Maximum Width	Collapsed Height	In-Use Height	Weight (lbs.)
Starter XL1240AL	up to 12'	47"	41"	45
Add-on XL640AL	adds 6'	47"	41"	20

Aisle Gate

Galvanized Steel

Stock No.	Maximum Width	Collapsed Height	In-Use Height	Weight (lbs.)
Aisle Gate	7'	40"	40"	12

Specifications

Finish: Galvanized steel. Powder coated yellow.

Webbing: 14 gauge steel 3/8" x 3/4" u-channel riveted back to back with zinc plated rivets.

Vertical Frame: 12 gauge steel 1-1/2" x 1-1/2" angle.

Feet: 14" wide.

Multiple Aisle Gates can be hooked together to form corners or any length. Light weight and welded on handle makes it easy to move from area to area.

Aluminum

Call factory for specifications.

Stock No.	Maximum Width	Collapsed Height	In-Use Height	Weight (lbs.)
Aisle Gate-AL	7'	40"	40"	6

