

MODEL MS – COMBINATION COMPRESSION & WIPER SEAL



FEATURE SUMMARY

- **Patented Superior Side Pad Design Seals Both Standard Trailers With a Compression Inner Pad And Trucks With Steps or Lift Gates with Outer Wiping Curtains**
- **High-Tear Abrasion Resistant Fabrics With Double Lock Stitched Seams**
- **Head & Side Curtains Inserted With Stays & Foam Bead on Inside Edge to Conform & Retain a Tight Seal Against Trailer Top & Sides**
- **Standard 8" Exposure Wear Pleats on Inner Pad**
- **Pressure Treated Superior Grade Backing & Head Frame Lumber**
- **Head Curtain With Overlapping Wear Pleats in Corners & TOUGH-SPLIT™ Stress Relief**
- **Rigid Raked Head Frame Channels Water to Sides**
- **Suitable for Door Openings Up To 9 Feet Wide x 10 Feet High**
- **Bottom Corner Draft Flaps & Galvanized Mounting Hardware Included**


DESCRIPTION

The MULTI-SEAL™ environmental dock control system is designed to provide a tight dual action seal against both the rear and sides of a truck or trailer. The compression style inner vertical pads deliver the desirable tight seal for standard trailers while the outer curtains provide a secondary wiper seal for standard trailers or trucks offset from the building wall due to rear tail gates or steps being present. The unique dual sealing function provides the most effective and versatile protection for personnel and cargo while loading and off-loading trailers. The truck backs into the dock bumpers compressing the inner side pads and top curtain while wiping the outer sides of the truck or trailer to effectively keep out inclement weather, dust and insects creating a more productive and safer environment.

Dual Compression & Wiper Seal For Standard Trailers



Wiper Seal for Trucks Equipped With Step or Tailgate



SPECIFICATON

Dock seal to be Model MS as manufactured by NORDOCK Inc. to suit door size of _____" wide x _____" high and a dock height of _____", bumper projection from wall of _____", and an incline _____ or decline _____ approach grade of _____%. Dock seal shall consist of two fabric covered foam side pads and one head curtain. Side pads to be constructed with 99% compression recovery polyurethane foam core continuously bonded to pressure treated superior backing lumber and fully wrapped with 40 oz. vinyl base fabric. The inner compression pads to have standard 40 oz. vinyl 8" exposure wear pleats and the outer wiper curtain to be velcro attached 40 oz. vinyl with compression stays and 24" yellow guide stripes to aid in driver positioning. Head curtain drop shall be 30" long or _____ to provide a minimum 6" overlap with the lowest trailer/truck to be serviced. The head curtain shall be equal to the overall unit width and have corner wear pleats and wind retention cords and with optional Tough-Split™ gussets to provide relief from tearing by corner of trailers. Configure dock seal if needed to suit a decline or incline approach grade, building wall setback and/or grade wall extension.

WARRANTY

NORDOCK guarantees that the Model MS Model dock seal will perform as described and to the full satisfaction of the purchaser for one-year from date of receipt. Consult your NORDOCK representative for assistance in choosing the correct size and options for your application.

OPTIONS:

- 50 oz. WT 90 WEARTOUGH® Base Fabric
- 4", 6" or 8" Exposure Wear Pleats
- 50 oz. WT-90 WEARTOUGH®Wear Pleats
- Tapered Sides for Decline/Incline Approach
- Fabric Covered Wood Build-Out

ADDITIONAL EQUIPMENT OPTIONS:

- Dock Levelers
- Vehicle Restraints
- RAINSHIELD™ Combination Trailer Top Seal.
- RAIN-STOP™ Combination Trailer Top Seal
- Loading Dock Lights

