

## MODEL FF – FOAM SIDED DOCK SHELTER



### FEATURE SUMMARY

- High-Tear Abrasion Resistant Fabrics With Double Lock Stitched Seams
- Kiln Dried Pressure Treated Superior Grade Backing & Head Frame Lumber
- 99 % Memory Foam Core Side Frame With Condensation Drainage System
- Prevents Damage From Off Center Trailers
- Head & Side Curtains Inserted With Stays & Foam Bead on Inside Edge to Conform & Retain a Tight Seal Against Trailer Top & Sides
- Head Curtain Provided With Overlapping Wear Pleats in Corners & Retention Cords
- 24" High Yellow Guide Stripes on Bottom of Pads for Accurate Truck Positioning
- Bottom Corner Draft Pads With "No Step" Imprint
- Translucent Frame Top Allows in Natural Light
- Most Suitable for Door Openings Up To 10 Feet Wide x 10 Feet High
- Galvanized Mounting Hardware Included



### DESCRIPTION

The WEARTOUGH® Series of full access dock shelters provide effective protection for personnel and cargo while loading and off loading trailers. The truck backs into the side and top curtains to help keep out inclement weather, dust and insects creating a more productive and safer environment while saving energy costs and increasing security.

### SPECIFICATON

Dock shelter(s) to be Model FF as manufactured by Nordock Inc. to suit door size of \_\_\_\_\_ wide x \_\_\_\_\_ high and dock height of \_\_\_\_\_ with a projection of \_\_\_\_\_ to provide 12"-18" projection beyond front face of dock bumpers. Each unit shall consist of (2) two fabric covered foam side pads with front curtains, one head frame and one head curtain. Side pads to be constructed with 99% compression recovery polyurethane foam core continuously bonded to pressure treated superior backing lumber and fully wrapped with the base fabric. The base fabric shall be \_\_\_\_\_. The front side and top curtain to have sewn in stays to keep tight against the truck and fabric shall be \_\_\_\_\_. Head curtain drop shall be 36" long or \_\_\_\_\_ to provide a minimum 6" overlap with the lowest trailer/truck to be serviced. The head curtain shall be equal to the overall unit width and have corner wear pleats and wind retention cords and with optional Tough-Split™ gussets to provide relief from tearing by corner of trailers \_\_\_\_\_. The unit shall include 24" high \_\_\_\_ or optional full height \_\_\_\_ yellow guide stripes to aid in trailer positioning.

### WARRANTY

Nordock guarantees that the FF Model of dock shelters will perform as described and to the full satisfaction of the purchaser for one-year from date of receipt. Consult your Nordock representative for assistance in choosing the correct size and options

### FABRIC OPTIONS:

22 oz. & 40 oz. Vinyl  
40 oz. Hypalon  
50oz. WT-90 WEARTOUGH®

### ADDITIONAL OPTIONS:

Dock Levelers  
Vehicle Restraints  
Loading Dock Lights

### SHELTER OPTIONS:

Tough-Split™ Head Curtain Gussets  
Terminator™ Trailer Door Gap Seal  
Full Height Yellow Guide Stripes  
Tapered Sides for Decline/Incline Approach



TERMINATOR™



TOUGH-SPLIT™